

Corrosion Resistant Reels | Stainless Steel Series

Stainless Steel Spring Retractable Reels

Air/Water/Oil - 3/8", 1/2", 3/4", 1" I.D.

Reelcraft's stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial-solvent handling. Also suitable for coastal, offshore and on-board ship in marine applications where the harsh environment of salt water spray requires the use of stainless steel hose reels. Swivels include Viton® O-rings.

Note: Standard latch parts are made from aluminium. Stainless latch parts are available as a standard option (except 80000 Series) by placing a -S at the end. Example: OLS-S. *Series 80000 and D80000 stainless reels have an aluminium fluid path and may not be suitable for all applications.

FEATURES

- ✓ Full-flow stainless steel shaft and swivel assures maximum product delivery.
Exception: Series 80000 - aluminum fluid path.
- ✓ Heavy duty brackets eliminate bending due to angular hose pull.
- ✓ Banded drive spring gives smooth automatic hose retrieval.
- ✓ Multi-position guide arm permits wall, floor, ceiling, pit or truck mounting.
- ✓ Nylon guide rollers reduce hose drag and abrasion.
- ✓ Pos-i-latch will maintain the desired working length of hose. Mechanism assures a positive latch of the hose.
- ✓ 7000 Series offers weatherproof gasketed spring motor, assures maximum service life.
- ✓ Vibration-proof self-locking fasteners assures assembly integrity.
- ✓ 304L grade of stainless steel.



Series 7000

General Use

Many versatile applications in corrosive or sanitary environments



Series D9000

Ultra Heavy Duty

Heavy duty dual pedestal for maximum strength

Model without hose & bumper	Shipping Weight		Pressure		Hose I.D.		Hose O.D.		(F)NPTF Inlet	Hose Length		Size Index
	lbs / kg	psi / bar	in / mm	in / mm	in	ft / m						
Low and Medium Pressure Reels Maximum Temperature 210° F (99° C)												
CA 5600 OLS	22 10	500 35	3/8 10	600 15	3/8	35	11	3/8	35	11	see pg. 9	
5600 OMS	24 11	3000 207	3/8 10	600 15	3/8	30	9	3/8	30	9	see pg. 9	
7800 OLS	41 19	500 35	1/2 13	.750 19	1/2	50	15	1/2	50	15	see pg. 10	
7600 OMS55	42 19	3000 207	3/8 10	.710 18	3/8	66	20	3/8	66	20	see pg. 10	
CA 7800 OMS	43 20	3000 207	1/2 13	.850 22	1/2	50	15	1/2	50	15	see pg. 10	
82000 OLS	81 37	500 35	1/2 13	.781 20	1/2	100	30	1/2	100	30	see pg. 13	
82000 OMS	83 38	1500 104	1/2 13	.820 21	1/2	75	23	1/2	75	23	see pg. 13	
83000 OLS	81 37	500 35	3/4 19	1.188 30	3/4	50	15	3/4	50	15	see pg. 13	
83000 OMS	83 38	1250 86	3/4 19	1.188 30	3/4	50	15	3/4	50	15	see pg. 13	
D83000 OLS	84 38	500 35	3/4 19	1.188 30	3/4	75	23	3/4	75	23	see pg. 13	
D84000 OLS	92 42	500 35	1 25	1.500 38	1	50	15	1	50	15	see pg. 13	
D9200 OLS	115 52	500 35	1/2 13	.781 20	1/2	100	30	1/2	100	30	see pg. 15	
D9300 OLS	116 53	500 35	3/4 19	1.188 30	3/4	75	23	3/4	75	23	see pg. 15	
D9400 OLS	117 53	500 35	1 25	1.500 38	1	50	15	1	50	15	see pg. 15	
D9200 OMS	118 54	3000 207	1/2 13	.820 21	1/2	75	23	1/2	75	23	see pg. 15	
D9300 OMS	118 54	3000 207	3/4 19	1.188 30	3/4	50	15	3/4	50	15	see pg. 15	

For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example D83000 OLS70.

Model without Hose & bumper	Shipping Weight		Pressure	(F)NPTF Inlet	I.D.	1/4	6	3/8	10	1/2	13	3/4	19	1	25	Size Index No. (see pg. 24)
	lbs / kg	psi / bar				in	O.D.	.530	14	.688	18	.845	22	1.188	30	
Manual Crank Medium Pressure Reels Maximum Temperature 210° F (99° C)																
CA HS18000 M	36	16	3000	207	1/2	425	130	300	91	200	61	---	---	---	---	1
HS28000 M	35	16	3000	207	1/2	625	191	450	137	300	91	---	---	---	---	2
HS19000 M	38	17	3000	207	3/4	425	130	300	91	200	61	75	23	---	---	1
HS29000 M	36	16	3000	207	3/4	625	191	450	137	300	91	125	38	---	---	2
HS37000 L	47	21	500	35	1	---	---	---	---	---	---	---	---	100	30	refer to reelcraft.com

Applications

- Restaurants
- Dairies
- Marinas
- Pharmaceutical
- Food Processing
- Ships