

Vehicle-Mount Hose Reels | Series 9000

Ultimate Duty Spring Retractable Reels

Air/Water/Oil/Grease - 1/2", 3/4", 1", 1 1/4", 1 1/2" I.D.

Series 9000 mobile base reels offer the greatest amount of stability for high volume air, water, diesel fuel and gasoline. Ideal for portable service trucks, permanent service or plant work areas.

A durable baked-on powder coat finish produces a rugged corrosion resistant product suitable for a wide variety of heavy duty applications. Basic reels without hose will handle air, water or oil; consult Reelcraft for other applications.



D9350 OLPBW

| No. | Dimensions - Size Index | | | | | |
|----------|-------------------------|---------|----------|---------|---------|---------|
| | 1 | | 2 | | 3 | |
| | in / mm | in / mm | in / mm | in / mm | in / mm | in / mm |
| A | 26 1/4 | 667 | 26 1/4 | 667 | 26 1/4 | 667 |
| B | 24 1/8 | 613 | 24 1/8 | 613 | 24 1/8 | 613 |
| C | 4 3/4 | 121 | 3 7/8 | 98 | 4 1/2 | 114 |
| D | 12 | 305 | 17 11/16 | 449 | 13 3/8 | 340 |
| E | 7 3/4 | 195 | 13 7/16 | 341 | 7 3/4 | 195 |
| F | 22 1/4 | 556 | 22 1/4 | 556 | 22 1/4 | 556 |
| G | 12 1/4 | 311 | 12 1/4 | 311 | 12 1/4 | 311 |
| H | 13 7/8 | 352 | 13 7/8 | 352 | 13 7/8 | 352 |
| J | 26 3/8 | 670 | 26 3/8 | 670 | 26 3/8 | 670 |

Four 1/4" (6mm) mounting holes.

Hose Guide Roller Position

A suffix code (see diagram) must be added after the model number to specify desired position. Reels are shipped in the BW position unless specified otherwise. FF9500/9600 in BW only.

| Model with Hose | Weight | | Pressure | | Hose I.D. | Hose O.D. | (M)NPTF Outlet | (F)NPTF Inlet | Hose Length | Model without hose & bumper | Weight | | Pressure | | Size Index No. |
|--|----------|-----------|-----------|-----------|-----------|-----------|----------------|---------------|-------------|-----------------------------|----------|-----------|----------|-----|----------------|
| | lbs / kg | psi / bar | psi / bar | psi / bar | | | | | | | lbs / kg | psi / bar | | | |
| Low Pressure Air/Water Reels Maximum Temperature 150° F (65° C) | | | | | | | | | | | | | | | |
| D9275 OLP | 122 | 55 | 300 | 21 | 1/2 21 | .750 19 | 1/2 | 1/2 | 75 23 | D9200 OLP | 115 | 52 | 500 | 35 | 1 |
| D9299 OLP | 127 | 58 | 300 | 21 | 1/2 13 | .750 19 | 1/2 | 1/2 | 100 30 | D9200 OLP | 115 | 52 | 500 | 35 | 1 |
| D9350 OLP | 140 | 64 | 250 | 17 | 3/4 19 | 1.075 27 | 3/4 | 3/4 | 50 15 | D9300 OLP | 115 | 52 | 500 | 35 | 1 |
| D9375 OLP | 152 | 69 | 250 | 17 | 3/4 19 | 1.075 27 | 3/4 | 3/4 | 75 23 | D9300 OLP | 115 | 52 | 500 | 35 | 1 |
| D9399 OLPBW | 143 | 65 | 250 | 17 | 3/4 19 | 1.075 27 | 3/4 | 3/4 | 100 30 | D9305 OLPBW | 115 | 52 | 500 | 35 | 3 |
| D9450 OLP | 157 | 71 | 250 | 17 | 1 25 | 1.375 35 | 3/4 | 1 | 50 15 | D9400 OLP | 115 | 52 | 500 | 35 | 1 |
| Not available with hose | | | | | 1 1/4 32 | 1.750 44 | 1 1/4 | 1 1/2 | 50 15 | FF9500 OLPBW | 125 | 57 | 600 | 41 | 2 |
| Not available with hose | | | | | 1 1/2 28 | 2.000 51 | 1 1/2 | 1 1/2 | 50 15 | FF9600 OLPBW | 135 | 61 | 600 | 41 | 2 |
| Medium Pressure Oil Reels Maximum Temperature 210° F (99° C) | | | | | | | | | | | | | | | |
| D9275 OMP | 131 | 59 | 2000 | 138 | 1/2 13 | .850 22 | 1/2 | 1/2 | 75 23 | D9200 OMP | 117 | 53 | 3000 | 207 | 1 |
| D9350 OMP | 142 | 64 | 1250 | 86 | 3/4 19 | 1.120 28 | 3/4 | 3/4 | 50 15 | D9300 OMP | 117 | 53 | 3000 | 207 | 1 |
| High Pressure Grease Reels Maximum Temperature 210° F (99° C) | | | | | | | | | | | | | | | |
| D9175 OHP | 153 | 69 | 4000 | 276 | 3/8 10 | .730 19 | 1/2 | 3/8 | 75 23 | D9100 OHP | 118 | 54 | 5000 | 345 | 1 |

Low pressure reels furnished standard with PVC hose. Medium pressure reels are furnished standard with S.A.E. 100 R1T one wire braid hose. High pressure reels furnished standard with SAE 100R2T two wire braid hose suitable for grease applications only. For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example D9300 OLP70. FF9500 and FF9600 models will have BSPP threads. **Note: To specify our heavy duty model, change prefix from D to E. Not available on FE9500 or FE9600. Modification** - Reels without hose can be modified to handle gasoline and diesel fuel, to order place prefix "F" before model number - example (FF9300 OLP).