

Series WST

Heavy duty PVC suction/discharge hose

Service Temperature Range

-4° F to 150° F

Actual service temperature range is
application-dependent.

Features & Benefits

- **Clear flexible PVC construction with synthetic reinforcement** — ideal for both suction and discharge applications... allows visual confirmation that material is flowing.
- **Gray exposed PVC helix design** — provides excellent strength characteristics while permitting hose to slide easily.
- **Smooth bore** — eliminates material build up.



General Applications

- Heavy duty suction and discharge.
- Rental/construction pumping.
- Fish suction.

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

Series	ID (In.)	Nominal		OD (mm)	Working Pressure (PSI)		Vacuum Rating (Inches Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs./ft.)
		ID (mm)	OD (In.)		68°F	104°F	68°F	104°F			
WST300	3	76.2	3.62	92.0	70	35	Full	28	6"	100/20	1.13
WST400	4	101.6	4.76	121.0	65	32	Full	28	8"	100/20	1.74
WST500	5	127.0	5.98	151.9	50	25	28	25	11"	100/20	2.95
WST600	6	152.4	7.17	182.1	50	25	28	25	13"	100/20	3.88

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.