

Double Bolt Clamps

A rugged, plated iron two-bolt clamp with machine bolts and hex nuts.

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment




with saddles

Hose OD		Plated Iron		Opt	Torque
from	to	Part #	Price/E	Qty	in ft. lbs.
3-32/64"	3-52/64"	400	\$18.15	25	40
3-50/64"	4-4/64"	431	21.95	20	40
4-2/64"	4-18/64"	463	19.35	20	40
4-16/64"	4-60/64"	525	24.10	10	60
4-32/64"	5-16/64"	550	25.10	10	60
5-8/64"	5-44/64"	600	27.10	10	60
5-44/64"	5-60/64"	639	30.90	10	60
5-60/64"	6-32/64"	675	29.45	10	60
6-32/64"	7-36/64"	769	32.60	10	60
7-44/64"	8-12/64"	818	47.15	5	125
8-16/64"	8-56/64"	875	46.95	5	125
8-60/64"	9-56/64"	988	57.70	5	125
9-60/64"	11-24/64"	1125	90.55	5	125
11-12/64"	13"	1275	101.35	3	125
12-12/64"	14"	1360	162.65	2	200
13-12/64"	15"	1450	151.25	2	200
15-4/64"	17-32/64"	1700	189.00	2	260

- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.
- Consult Dixon when using double bolt clamps on helical wire hose.

SAFETY
ALERT



without saddles

Hose OD		Plated Iron		Opt	Torque
from	to	Part #	Price/E	Qty	in ft. lbs.
1-8/64"	1-12/64"	J48	\$6.45	100	15
1-12/64"	1-24/64"	J49	8.05	50	21
1-28/64"	1-34/64"	JX49	10.40	25	21
1-40/64"	1-52/64"	DL14	11.95	25	40
1-48/64"	2-3/64"	DL20	11.65	25	27
2-7/64"	2-19/64"	DL24 ¹	11.65	25	27
2-20/64"	2-40/64"	DL32 ¹	12.90	25	40
2-32/64"	2-48/64"	DL275	15.65	25	40
2-48/64"	3-4/64"	DL306	17.50	20	60
3-4/64"	3-24/64"	DL328	18.60	20	60
3-16/64"	3-32/64"	DL350	18.25	20	60

¹ investment carbon steel

Single Bolt Clamps



- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.

SAFETY
ALERT

Hose OD		Plated Iron		Torque
from	to	Part #	Price/E	in ft. lbs.
56/64"	1"	2	\$16.00	6
62/64"	1-8/64"	3	18.50	6
1-4/64"	1-12/64"	4	18.50	6
1-10/64"	1-16/64"	5	18.50	6
1-16/64"	1-24/64"	6	18.50	6
1-22/64"	1-28/64"	7	20.30	6
1-28/64"	1-36/64"	8	21.10	6
1-34/64"	1-44/64"	9	20.30	6
1-42/64"	1-48/64"	10	20.30	6
1-48/64"	1-56/64"	11	21.25	6
1-56/64"	2-2/64"	12	20.65	6
2"	2-8/64"	13	21.40	12
2-8/64"	2-18/64"	14	22.55	12
2-16/64"	2-26/64"	15	24.50	12

Hose OD		Plated Iron		Torque
from	to	Part #	Price/E	in ft. lbs.
2-24/64"	2-32/64"	16	\$21.90	12
2-32/64"	2-40/64"	17	22.00	12
2-40/64"	2-56/64"	18	24.70	12
2-56/64"	3-4/64"	19	24.00	12
3-4/64"	3-16/64"	20	24.00	12
3-16/64"	3-28/64"	21	27.00	12
3-28/64"	3-40/64"	22	27.00	21
3-40/64"	3-52/64"	23	34.35	21
3-52/64"	4-8/64"	24	33.35	21
4-8/64"	4-20/64"	25	34.45	21
4-16/64"	4-32/64"	26	36.10	21
4-28/64"	4-40/64"	27	39.00	21
4-40/64"	4-56/64"	X27	38.10	21
4-56/64"	5-16/64"	28	38.10	21