



ENGINEERING AND TECHNICAL DATA

Bendway® A

March 2007

Construction: Single-ply helically corrugated aluminum alloy hose with a four-ply finished seam that is folded flat and crimped for tightness and strength



Product Features:

- " Light weight & hand bendable allowing for elbows & turns to be formed easily during installation
- " Self-supporting construction allows for bends to stay in place
- " Resists metal fatigue, weathering, & most corrosive fumes & chemicals
- " Not recommended for continuous flexing
- " Hose connectors available
- " Wall thickness = .008"

Applications: Recommended for industrial air movement and fume control applications.

Temperature Range: -100°F to 400°F

Diameter Range (Inches I.D.): 2.00-12.00 Inch I.D.

Standard Length: 5 & 10 Feet

I.D. Tolerances (Inches): -0.00 to +0.250 Inch

Standard Color: Silver

End Finish: Plain Cut (connectors available)

Markets: "Chemical Fumes "Circuit Board Cooling "Exhaust Systems "HVAC "Oil Mist "Ozone
"Pollution Control "Ventilation



A SCHAUBURG HOSE TECHNOLOGY COMPANY

1510 Armstrong Road, P.O. Box 4275
Warsaw, IN 46581-4275

Telephone 574-267-7909 • Toll Free 800-343-0428 • Fax 574-269-7491 • Toll Free Fax 800-382-8464
sales@flexaust.com • www.flexaust.com



ENGINEERING AND TECHNICAL DATA

Bendway® A

(Page 2)

March 2007

SIZE INSIDE DIMENSION (INCHES)	APPROXIMATE WEIGHT (LBS./FT.)	MINIMUM CENTERLINE BEND RADIUS (INCHES)	COMPRESSION RATIO	MAXIMUM RECOMMENDED NEGATIVE PRESSURE (IN./HG.)	MAXIMUM RECOMMENDED POSITIVE PRESSURE (PSI)
2	.113	4	N/A	N/A	N/A
3	.167	5.7	N/A	N/A	N/A
4	.2	7.48	N/A	N/A	N/A
5	.25	9.34	N/A	N/A	N/A
6	.3	11.2	N/A	N/A	N/A
7	.35	13.06	N/A	N/A	N/A
8	.35	14.96	N/A	N/A	N/A
9	.4	16.82	N/A	N/A	N/A
10	.44	18.68	N/A	N/A	N/A
12	.53	22.39	N/A	N/A	N/A

Note: Technical data based on 2 ft. straight lengths of hose @ 72° F.

Disclaimer: The proper use and maintenance of hose and/or duct manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all Flexaust products and we welcome comments and suggestions from our customers.



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY

1510 Armstrong Road, P.O. Box 4275

Warsaw, IN 46581-4275

Telephone 574-267-7909 • Toll Free 800-343-0428 • Fax 574-269-7491 • Toll Free Fax 800-382-8464

sales@flexaust.com • www.flexaust.com